



TECHNICAL DATA SHEET

1. TECHNICAL SPECIFICATION

PRODUCT	CHLORINATED PARAFFIN 70	MODEL	CP-70
SUBJECT		STANDARD VALUE	
APPEARANCE		WHITE TO PALE YELLOW POWDER	
CHLORINE CONTENT (%)		68~72	
SOFTENING POINT (°C)		≥90	
THERMAL STABILITY INDEX (%)		≤0.3	
DECOMPOSITION TEMPERATURE (°C)		≥170	
FINENESS (RESIDUE ON 40mesh SIEVE)		≤0.5	

2. PACKAGING & STORAGE:

25KG/BAG, WITHOUT PALLET, 23MT/20'GP

25KG/BAG, PALLETIZED, 18MT/20'GP

THE PRODUCT SHOULD BE STORED UNDER DRY AND CLEAN CONDITIONS IN ITS ORIGINAL PACKING. THE MOISTURE MAY INCREASE IF NOT STORED UNDER DRY CONDITIONS.

3. RECOMMEND APPLICATION:

USED AS FLAME RETARDANT ADDITIVE IN THE PRODUCTION OF RUBBER CONVEYOR BELT, FLAME RETARDANT COATING (PAINT).

4. SHIPPING INFORMATION:

TRANSPORTATION CLASSIFICATION: NOT REGULATED FOR TRANSPORTATION



5. CHEMICAL REGISTRATION NUMBERS:

CAS NO.: 63449-39-8

EINECS NO.: 287-478-6